

## Processing instructions

Repair Paste Epoxy Boards is a light blue, two-component epoxy paste for repairing small holes or chipping.

Mix both components 1:1 (volume or weight). Due to its different colours it can easily be identified when the components are mixed.

When applying the paste, make sure to avoid air entrapments. After some 30 minutes at 21 °C the repaired area can be reworked.

Mixing ratio: 100:100 by weight or by volume

Geltime: about 4 - 5 minutes at 21°C

## In General

Repair paste epoxy boards comp. A

Colour: blue

Density: 0,70 g/cm<sup>3</sup>

Repair paste epoxy boards comp. B

Colour: white

Density: 0,70 g/cm<sup>3</sup>

Unit: 0,400 kg-Kit (0,200 kg Comp. A/ 0,200 kg Comp. B)

## Storing

Storage at room temperature 18 - 25°C.

Already opened containers should be closed immediately after use and should be used as soon as possible.

Shelf life 6 months.

## Safety measure

Please follow the precaution instructions of the Government Safety Organisation of the chemical industry when working with this material. Please follow safety advices !

## Waste Disposal

According to arrangement with local authorities cured material can be disposed as domestic or commercial waste.

Non-cured products are waste which is subject to inspection and has to be disposed accordingly.

In case of further questions please do not hesitate to contact our Department for Product Safety.

The instructions and recommendations are given in good faith and are based on long experience and careful tests. Since the conditions of use are beyond our control, and due to versatility of applications and working methods, we can't give any guarantee. All information are non-binding and are no guarantee for special characteristics or properties of the product. Despite information given from **ebalta** the customer has to make his own tests regarding applications and processing. If any special warranty is requested, written agreement on this subject is essential.